



PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of PREMIUM SERIE YS9015AJ

Product	Product Category	Coating
PTFE GLASS FABRIC	PREMIUM SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000 mm	39.5 inches
Thickness	0.15 mm	0.006 inches
Coated weight	315 g/m ²	9.29 oz/yd ²
PTFE content	66%	66%
Tensile Stength	250 N/cm Warp	143 lbs/inches Warp
	210 N/cm Fill	120 lbs/inches Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® offering excellent smooth and high gloss surface coating, which has also super abrasion resistance and high tensile strength.

Applications of PTFE coated fiberglass include release sheet for heat press machines, belting for food industry, Non stick baking liner or oven liner, electrical insulation and industrial processing.

0.15mm Teflon fiberglass is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
Jiangsu Eson New Material Co.,Ltd
Taixing Youngsun FL-Plastics Co.,Ltd
Western End of South Third Ring Road, Taixing, Jiangsu, China
Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com